

I NEED SPECIFICATIONS



Panel	TFT Active Matrix LCD, Slim Cabinet VIS: 15" (38.1cm), Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Basic
Pixel / Dot Pitch	0.297mm x 0.297mm
Viewable Image Size (Diagonal)	15"
Display Area	304mm x 228mm
Brightness	250 cd/m² (typ)
Contrast Ratio	450:1 (typ)
Typ. Response Time (tr+tf)	16ms
Viewing Angle	Horizontal: 120 Degrees Vertical: 100 Degrees
Compatibility	VESA, XGA, SVGA, VGA Mac® Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~60KHz Vertical: 55~75 Hz
Pixel Frequency	80 MHz
Maximum Resolution	1024x768@75Hz
Recommended Resolution	1024x768@60Hz
Resolution Supported	740x400@70Hz, 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz
Colours	16.7M
Signal Input	Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative
Connectors	RGB Signal: 15-pin D-sub Male (Attached) Power: 3-pin Plug (CEE22)
Power Source	Power Input: Universal 100~240VAC, 50/60Hz
Power Consumption	25Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR ®	Yes
User Control	Stand-by Power, Auto Config
Function	Brightness, Contrast, Focus, Clock, H/V Position, Language, Colour Temperature (C1, C2), Reset, Exit, RGB
OSD Languages	English, German, French, Spanish, Italian
Speaker	2 x 1.5Watt Volume, Earphone Output
Emissions Standard	TC003
Regulations	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows® XP Logo
Other Features	VESA 75mm Wall Mountable*, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 350x84x350 mm Carton: 400x125x400 mm
Weight	Net: 2.8Kg Gross: 3.8Kg
Loading Qty w/ pallet	40" 2755 pcs 20" 1330 pcs
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice.

* Wall mount arm & bracket not included.

** Available: Q3/2005

*** Available in RGB Analogue mode only.